

## NewGlassTechnology

☐ Inquiry ☐ Order	-
NewGlassTechnology Where progress never stops	Contact person:  Telephone:
Tel: 003293955599 Fax: 003293955099 info@newglasstech.com http://newglasstech.com	Quotation No.:  Commission:
Type:  SF 50 non thermally insulated aluminium system non thermally insulated aluminium system with solid timber cladding of all visible inside aluminium profiles (except bottom rail) Type of timber and finish:	
Opening direction: Inwards opening outwards opening	
Parking bay: Typ 1 Typ 2 Typ 3	Special solution
Number of panel: to the left to the right (Please draw a floor plan or a view sketch for better understanding)	
Dimensions: Width: (Total unfolding) Height: (incl. possible floor recession)	
Colour: RAL 7016 RAL 9006 RAL 9007 RAL 9016 E6-EV1 Special colour Pre anodizing	
Handle colour: E6-EV1 powder RAL 9011 RAL 9016 Special colour	
Glazing:  Standard Insulated glass 2 x 4/20 c without glass: prepared for Special glass:	
Ceiling connection: without overlay profile with ov	erlay profile inside
Ground connection: with floor sockets with flush bottom track (height incl. floor recession)	
	perated from both sides) (operated from both sides)
	, push handle, 2 x dead lock th PZ and handle at both sides t to the right.

Please enclose floor plan resp. view sketch and remarks (please use inside view)



