

Inquiry     Order



Where progress never stops

Tel: 003293955599

Fax: 003293955099

[info@newglasstech.com](mailto:info@newglasstech.com)<http://newglasstech.com>

Contact person: \_\_\_\_\_

Telephone: \_\_\_\_\_

Quotation No.: \_\_\_\_\_

Commission: \_\_\_\_\_

Type:             SF 50    non thermally insulated aluminium system  
 SF 50c    non thermally insulated aluminium system with solid timber cladding  
of all visible inside aluminium profiles (except bottom rail)  
Type of timber and finish: \_\_\_\_\_

Opening direction:     inwards folding     outwards folding

Number of panel    \_\_\_\_\_ to the left    \_\_\_\_\_ to the right    (Please draw a floor plan or a view sketch for better understanding)

Dimensions:    Width: \_\_\_\_\_ (Total unfolding)    Height: \_\_\_\_\_ (incl. possible floor recession)

Colour:     RAL 7016     RAL 9006     RAL 9007     RAL 9016     E6-EV1     Special colour \_\_\_\_\_  
 Pre anodizing

Colour of hinges:     E6-EV1 powder     RAL 9011     RAL 9016     Special colour \_\_\_\_\_

Handle colour:     E6-EV1 powder     RAL 9011     RAL 9016     Special colour \_\_\_\_\_

Glazing:             Standard heat protection glass 2 x 4/20 SZR Ug 3.0  
 without glass: prepared for \_\_\_\_\_ mm  
 Special glass: \_\_\_\_\_ (Please indicate exact designation)

Floor connection:     with weathered bottom track  
 with flush bottom track (height incl. floor recession)

Locking of turn panel:     Standard (shoot bolt lock operated from inside only)  
 Shoot bolt lock with PZ (operated from both sides)  
 Roller latch + 2 x dead lock + HEWI push handle  
 Anti-draft lock with mushroom head and 4 point locking,  
latch and profile cylinder (operable on both sides)  
 Pull handle for turn panel, outward folding system  
 other: \_\_\_\_\_

Additional safety:     Twin-Lock  
 WK2-Safety package

Please enclose floor plan resp. view sketch and remarks (please use inside view)